

16 - Other Information

Disclaimer: The information contained in this MSDS is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS), and European Union Directive 1907/2006/EEC (REACH). Hazard symbols and risk phrases are based on maximum listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS) or the European Union (EU/EEC) directive 609/2006/EEC and are considered trade secrets under US Federal Law (29CFR and 40CFR), Canadian Law (Health Canada Legislation), and European Union Directives.

SMOOTH-ON**Material Safety Data Sheet**

Smooth-Cast 300 Series

MSDS No. 476

Date of Preparation: December 23, 2009

Revision: 0009

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: Smooth-Cast 300, 300Q, 305 and 310 Part A
General Use: Polyurethane Elastomer
Manufacturer: Smooth-On Inc., 2000 St. John St., Easton PA 18042
Phone: (610) 252-5800, **FAX:** (610) 252-6200

Emergency Contact: Chem-Tel
Domestic: 800-255-3924
International: 813-248-0585

Section 2 - Hazards Identification**Hazard Designation:**

Europe



Xn = Harmful

Canada

**Information pertaining to particular dangers****R20:** Harmful by inhalation**R36/37/38:** Irritating to eyes, respiratory system and skin**R40:** Limited evidence of a carcinogenic effect**R48/20:** Harmful; danger of serious damage to health by prolonged exposure through inhalation

Classified according to Articles 6 & 7 of Directive 1999/45/EC

Section 3 - Composition / Information on ingredients

Component	ACGIH TWA	OSHA PEL	Hazard Designation	Weight Percent (%)
4,4' Methylene bis(phenylisopropylate) (MDI)	0.005 ppm	0.02 ppm	Xn	55-60
CAS Number: 4000-92-6				
EINECS Number: 202-368-0				

Section 4 - First Aid Measures

Inhalation: Remove source(s) of contamination and move victim to fresh air. If breathing has stopped, give artificial respiration, then oxygen if needed. Contact physician immediately.

Eye Contact: Flush eyes with plenty of water. If irritation persists, seek medical attention.

Skin Contact: In case of skin contact, wash thoroughly with soap and water; remove contaminated clothing and launder before reuse; seek medical attention if rash develops.

Ingestion: Do not induce vomiting unless instructed by a physician. Contact physician immediately.

After first aid, get appropriate in-plant, paramedic, or community medical support.